



CFZ-15S
CFZ-20S



Detail

CFZ-30S
CFZ-40S



Control Panel



Tube



Durable wheel

AWAC[®]

DEHUMIDIFIER

CFZ Series

- Large capacity
- Accurate humidity control
- Easy to move
- Auto defrost
- Electronic control with :24hr timer
- Fail code display
- Solid and durable structure
- Humidity setting
- Three minutes delay protection for compressors
- Dual protection by pressure and temperature
- Digital display for ambient humidity

Model	CFZ-15S	CFZ-20S	CFZ-30S	CFZ-40S
Dehumidifying Capacity(30 C , 80%)	360L/Day	480L/Day	720L/Day	960L/Day
Supply Voltage	380V/50Hz	380V/50Hz	380V/50Hz	380V/50Hz
Rated Input Current	10.5A	13.5A	22.8A	33.5A
Rated Input Power	6.2KW	8.1KW	8.1KW	19.8KW
Air Circulation	4000m ³ /h	5000m ³ /h	8000m ³ /h	10000m ³ /h
Scope of Application	400~550m ²	550~800m ²	800~1000m ²	1000~1500m ²
Body Dimension	1187*500*1748mm	1187*500*1748mm	1387*720*1894mm	1387*720*1894mm
Net Weight	216kg	240kg	380kg	430kg
Loading Quantity(20'/40')	22/46	22/46	8/16	8/16