



AWAC[®] EL-820D-D DEHUMIDIFIER



Control panel

SPECIFICATION

FACTORY MODEL	EL-820D-D	WATER DRAINAGE	Continuous drainage by pipe
Sheel	Powder coating steel; any color is ok	PIPE DIAMETER	Φ16mm
REFRIGERANT TYPE	R134a	POWER CONNECTION TYPE	Screw TERMINAL ELOCK
Compressor oil	Synthetic oil	POWER CONNECTION TYPE Plug	Customer request
DEHUMIDIFICATION CAPACITY	20L/D	Wire gauge Sq.m	0.75
PINTS/D (30C / 80RH)	35	Air Flow M3/H	400
Control type	Micro-computer	Fan motor quantity	1
VOLTAGE V	220V	CLEANAELE AIR FILTER	HEPA air filter
HZ	50HZ	Humidity seting RANGE	10 - 99%
PHASES	Single	Humidity PRECISION CONTROL deviation	≤+8%
WATTS	280W	SENSOR	Humidity/ Temperature sensor
AMPS	4.0	TIMMER SETING	1 - 24 hours
Cooling capacity BTU/HR	2000	WORK TEMPERATURE	5-38°C
COMPRESSOR Brand	Kangpusi	LEVEL NOICE	45dB
COMPRESSOR TYPE	ROTATORY	DIMENSION CMS	710*445*270mm
COMPRESSOR QUANTITY	1	WEIGHT	30KG
DEFROST TYPE	COMPRESSOR STOPPING, THROUGH FAN MOTOR(AUTOMATICLY)	USAELE FLOOR AREA (MTS2)	10-20
CHARGING GAS KIT ADJUSTAELE	Yes	WARRANTY	1 YEAR
		CONDENSATE PUMP	NO