



AWAC[®] EL-830D-D DEHUMIDIFIER



Control panel

SPECIFICATION

MODEL	EL-830D-D	WATER DRAINAGE	Continuous drainage by pipe
Sheel	Powder coating steel; any color is ok	PIPE DIAMETER	Φ16mm
REFRIGERANT TYPE	R134a	POWER CONNECTION TYPE	Screw TERMINAL ELOCK
Compressor oil	Synthetic oil	POWER CONNECTION TYPE Plug	Customer request
DEHUMIDIFICATION CAPACITY	30L/D	Wire gauge Sq.m	0.75
PINTS/D (30C / 80RH)	50	Air Flow M3/H	520
Control type	Micro-computer	Fan motor quantity	1
VOLTAGE V	220V	CLEANAELE AIR FILTER	HEPA air filter
HZ	50HZ	Humidity seting RANGE	10 - 99%
PHASES	Single	Humidity PRECISION CONTROL deviation	≤±8%
WATTS	330W	SENSOR	Humidity/ Temperature sensor
AMPS	4.8	TIMMER SETING	1 - 24 hours
Cooling capacity BTU/HR	2300	WORK TEMPERATURE	5-38°C
COMPRESSOR Brand	Kangpusi	LEVEL NOICE	45dB
COMPRESSOR TYPE	ROTATORY	DIMENSION CMS	710*445*270mm
COMPRESSOR QUANTITY	1	WEIGHT	32KG
DEFROST TYPE	COMPRESSOR STOPPING, THROUGH FAN MOTOR(AUTOMATICLY)	USAELE FLOOR AREA (MTS2)	30-50
CHARGING GAS KIT ADJUSTAELE	Yes	WARRANTY	1 YEAR
		CONDENSATE PUMP	NO