



AWAC[®] EL-890D-D DEHUMIDIFIER



Control panel

SPECIFICATION

| | | | |
|-----------------------------|--|--------------------------------------|------------------------------|
| FACTORY MODEL | EL-890D-D | WATER DRAINAGE | Continuous drainage by pipe |
| Sheel | Powder coating steel; any color is ok | PIPE DIAMETER | Φ16mm |
| REFRIGERANT TYPE | R410a | POWER CONNECTION TYPE | Screw TERMINAL ELOCK |
| Compressor oil | Synthetic oil | POWER CONNECTION TYPE Plug | Customer request |
| DEHUMIDIFICATION CAPACITY | 90L/D | Wire gauge Sq.m | 1 |
| PINTS/D (30C / 80RH) | 158 | Air Flow M3/H | 1000 |
| Control type | Micro-computer | Fan motor quantity | 1 |
| VOLTAGE V | 220V | CLEANAELE AIR FILTER | HEPA air filter |
| HZ | 50HZ | Humidity seting RANGE | 10 - 99% |
| PHASES | Single | Humidity PRECISION CONTROL deviation | ≤+8% |
| WATTS | 1300W | SENSOR | Humidity/ Temperature sensor |
| AMPS | 11.2 | TIMMER SETING | 1 - 24 hours |
| Cooling capacity BTU/HR | 10742 | WORK TEMPERATURE | 5-38°C |
| COMPRESSOR Brand | HITACHI | LEVEL NOICE | 45dB |
| COMPRESSOR TYPE | ROTATORY | DIMENSION CMS | 920*570*440mm |
| COMPRESSOR QUANTITY | 1 | WEIGHT | 53KG |
| DEFROST TYPE | COMPRESSOR STOPPING, THROUGH FAN MOTOR(AUTOMATICLY) | USAELE FLOOR AREA (MTS2) | 80-120 |
| CHARGING GAS KIT ADJUSTAELE | Yes | WARRANTY | 1 YEAR |
| | | CONDENSATE PUMP | NO |